



NAVF

FLAT TOP *Cargo*

STANDARD SPECIFICATIONS:

- Dexter Sprung Axle(s)
- NEV-R-ADJUST Brakes & EZ Lube Hubs (Tandems)
- Integrated Triple Tube Tongue
- Flushlock Curbside Door - 24" (5' wides)
- Flushlock Curbside Door - 32" (6' and 7' Wides)
- Stainless Steel Holdbacks
- Bonded Exterior Skin - .030 Aluminum
- 1 Piece Seamless Aluminum Roof
- Single Rear Swing Door on 5' wides
- Double Rear Swing Door on 6' and 7's.
- 2" Coupler on Single Axle Models
- 2-5/16" Coupler on Tandems
- 3/4" Exterior Grade Plywood Floor
- 24" ATP Stone Guard
- Tongue Jack - 2K - Top Wind
- LED Exterior Lighting
- 16" O/C Roof Bows
- 24" O/C Walls - Flat Top
- 24" O/C Floor - Tube Cross Members
- Lauan Interior Walls: 5' Wide
- 3/8" Plywood Interior Walls: 6', 7'
- 12v Dome Light(s) 1/Single, 2/Tandem
- 15" Silver Mod Radials 205 75 R15

THE SPECS

Model	Axles	Box Length	Std. Int. Ht.	Plus 6"	Plus 12"
NAV85F	2500lbs.	8'	58.5"	64.5"	70.5"
NAV105SF	2500lbs.	10'	58.5"	64.5"	70.5"
NAV125SF	2500lbs.	12'	58.5"	64.5"	70.5"
NAV106SF	2990lbs.	10'	72.75"	78.75"	84.75"
NAV126SF	2990lbs.	12'	72.75"	78.75"	84.75"
NAV126TF	2/3500lbs.	12'	72.75"	78.75"	84.75"
NAV146SF	2990lbs.	14'	72.75"	78.75"	84.75"
NAV146TF	2/3500lbs.	14'	72.75"	78.75"	84.75"
NAV127SF	2990lbs.	12'	72.75"	78.75"	84.75"
NAV127TF	2/3500lbs.	12'	72.75"	78.75"	84.75"
NAV147TF	2/3500lbs.	14'	72.75"	78.75"	84.75"
NAV167TF	2/3500lbs.	16'	72.75"	78.75"	84.75"
NAV187TF	2/3500lbs.	18'	72.75"	78.75"	84.75"
NAV207TF	2/3500lbs.	20'	72.75"	78.75"	84.75"
5' Rear Openings:	52"W		53.25"H	59.25"H	65.25"H
6' Rear Openings:	64"W		67.25"H	73.25"H	79.25"H
7' Rear Openings:	76"W		67.25"H	73.25"H	79.25"H



Standard Rear Doors

Optional Tribal Slash

For Additional Specs & Photos, go to:

neomfg.com

e-mail: sales@neomfg.com

21900 US 12 Sturgis, MI 49091
269.503.7630

