



NAVR

ROUND TOP

Cargo

STANDARD SPECIFICATIONS:

- Dexter Sprung Axle(s)
- NEV-R-ADJUST Brakes & EZ Lube Hubs (tandems)
- Integrated Triple Tube Tongue
- Flushlock Curbside Door - 24" (5' wides)
- Flushlock Curbside Door - 32" (6' and 7' Wides)
- Stainless Steel Holdbacks
- Bonded Exterior Skin - .030 Aluminum
- 1 Piece Seamless Aluminum Roof
- Single Rear Swing Door on 5' wides
- Double Rear Swing Door on 6' and 7' s.
- 2" Coupler on Single Axle Models
- 2 5/16" Coupler on Tandems
- 3/4" Exterior Grade Plywood Floor
- Eagle Stone Guard - 24" ATP
- Tongue Jack - 2K - Top Wind
- LED Exterior Lighting
- 16" O/C Roof Bows
- 16" O/C Walls - Round Top
- 24" O/C Floor - Tube Cross Members
- Lauan Interior Walls: 5' Wide
- 3/8" Plywood Interior Walls: 6', 7'
- 12v Dome Light(s) 1/Single, 2/Tandem
- 15" Silver Wheels, Bias Tires



THE SPECS

Model	Axles	Box Length	Std. Int. Ht.	Plus 6"	Plus 12"
NAV85R	2500lbs.	8'	58.5"	64.5"	70.5"
NAV105SR	2500lbs.	10'	58.5"	64.5"	70.5"
NAV125SR	2500lbs.	12'	58.5"	64.5"	70.5"
NAV106SR	2990lbs.	10'	72.75"	78.75"	84.75"
NAV126SR	2990lbs.	12'	72.75"	78.75"	84.75"
NAV126TR	2/3500lbs.	12'	72.75"	78.75"	84.75"
NAV146SR	2990lbs.	14'	72.75"	78.75"	84.75"
NAV146TR	2/3500lbs.	14'	72.75"	78.75"	84.75"
NAV127SR	2990lbs.	12'	78.5"	84.5"	90.5"
NAV127TR	2/3500lbs.	12'	78.5"	84.5"	90.5"
NAV147TR	2/3500lbs.	14'	78.5"	84.5"	90.5"
NAV167TR	2/3500lbs.	16'	78.5"	84.5"	90.5"
NAV187TR	2/3500lbs.	18'	78.5"	84.5"	90.5"
NAV207TR	2/3500lbs.	20'	78.5"	84.5"	90.5"

REAR DOOR OPENINGS:	5' 52"W	53.25"H	59.25"H	65.25"H
	6' 64"W	67.25"H	73.25"H	79.25"H
	7' 76"W	73.25"H	79.25"H	85.25"H



Optional NXP Ramp Door



Standard Bar-Lock Swing Doors

For Additional Specs & Photos, go to:

neomfg.com

e-mail: sales@neomfg.com

21900 US 12 Sturgis, MI 49091
269.503.7630

